

FRED SHEARER & SONS, INC. ESTABLISHED 1916

Job Hazard Analysis			JHA # 20	
Job/Task Title: Motor Vehicle Operation				
Safe Job Procedure:			Revised 1/2024	
This JHA is for the safe operation of company vehicles. Special emphasis is placed on performing a pretrip inspection and defensive driving.				
Required PPE: Work Boots – Have available Hard Hat, Hi-Vis Vest, and Cut-4 Gloves				
Review JHA's: 26,29 Material Handling, Industrial/Rough Terrain Forklift				
Step #1 Preparing to Depart				
Steps to Complete Job	Hazards	<u> </u>	entive Measures	
Vehicle inspection and	Worker has the potential	1) Stretch and flex before beginning of shift and		
setting route.	to be exposed to strains,		throughout the shift when	
	sprains, and trips.		er eliminate muscle strains. ess a valid driver's license and	
			to drive a company vehicle.	
			rspection must be performed,	
			d out before using any	
		company vehicle. A	ny vehicle failing the pre-trip	
			n out of service until the	
		problem has been o	corrected.	
Step #2 Driving Company Vehicles				
Steps to Complete Job	Hazards		ntive Measures	
Operating a company	Worker has the		the destination is, and what	
vehicle.	potential to be exposed	route is going to b		
	to multiple types of hazards.		sengers must be wearing	
	Hazarus.		chicle is being driven.	
		while driving.	limits and regulatory laws	
			tronics must be done in a	
		"Hands Free" mod		
			nust be engaged, and	
			vehicle is being loaded or	
		unloaded.	vernere is being loaded of	
			utilize one of the following	
		_ ·	A back-up camera, A back-	
	I	which backing up.	A back up camera, A back-	



FRED SHEARER & SONS, INC. ESTABLISHED 1916

	up alarm, Double horn prior to backing up, or a spotter. 7) No one allowed to ride in the bed of any vehicle at any time. 8) Secure or cover all loads to prevent movement.			
Step #3 Operating a Lift Gate				
Steps to Complete Job	Hazards	Preventive Measures		
Using lift gate to load and unload materials and equipment.	Caught between, runaway loads, trip hazards, fall hazards.	 Perform a visual inspection prior to use each day checking for loose, missing or worn parts and leaking fluids. Lift gate operators should not perform any maintenance. Repairs and maintenance should be performed by an authorized service technician. Never enter the area beneath a raised lift gate. Ensure proper hand/foot placement. Always be aware of pinch points. 		